

ACE DECOFLOOR 150 HARDENER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1 Product identifier.

Product Name: ACE DECOFLOOR 150 HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Professional exclusive use.

For treating concrete, steel and other surfaces.

1.3 Details of the supplier of the safety data sheet.

Company: ACE COATINGS

Address: Campo Sagrado, 1133205

City: Gijón

Province: Asturias

Telephone: +34 985 323 328

E-mail: info@acecoatings.com

Web: www.acecoatings.com

1.4 Emergency telephone number: (Available 24 hours)

Telephone number

+34 977 822 245 (Only available during office hours)

EUROPE: +32 35 75 1234

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if inhaled.

STOT SE 3 : May cause respiratory irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

**ACE DECOFLOOR 150
HARDENER**

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P321 Specific treatment (see ... on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to ...

EUH statements:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

Contains:

2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol

Hexamethylene diisocyanate, oligomers

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

Dirección Corporativa:

ACE COATINGS S.L.
Campo Sagrado, 11
33205 - Gijón - España (Spain)



+34 985 323 328
www.acecoatings.com
info@acecoatings.com

ACE COATINGS LATAM SPA
Av/ Apoquindo 3885 Piso 18
Las Condes-Santiago de Chile
+56 931 865 276

Safety Data Sheet

Conforms to Regulation (EC) n° 1907/2006
(REACH), Anexo II – United Kingdom (UK)

ACE DECOFLOOR 150 HARDENER

The product may have the following additional risks:
Get away from the water

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.
Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 164250-92-4	2-Oxepanone, polymer with 1,6-diisocyanatohexane and 1,6-hexanediol	54 - 75 %	Acute Tox. 4, H332 - STOT SE 3, H335 - Skin Sens. 1, H317	-
CAS No: 28182-81-2 EC No: 500-060-2	Hexamethylene diisocyanate, oligomers	1 - 50 %	Skin Sens. 1, H317	-
Index No: 615-011-00-1 CAS No: 822-06-0 EC No: 212-485-8	[2] hexamethylene-di-isocyanate	0.1 - 0.5 %	Acute Tox. 3 *, H331 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Resp. Sens. 1, H334: C ≥ 0,5 % Skin Sens. 1, H317: C ≥ 0,5 %

(*)The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

ACE DECOFLOOR 150 HARDENER

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance. The use of personal protective equipment is recommended for people providing first aid (see section 8).

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

ACE DECOFLOOR 150 HARDENER

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

ACE DECOFLOOR 150 HARDENER

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
hexamethylene-di-isocyanate	822-06-0	Éire [1]	Eight hours	0,005	
			Short term		

[1] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
hexamethylene-di-isocyanate CAS No: 822-06-0 EC No: 212-485-8	DNEL (Workers)	Inhalation, Chronic, Local effects	0,035 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	0,035 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Safety Data Sheet

Conforms to Regulation (EC) n° 1907/2006
(REACH), Anexo II – United Kingdom (UK)

ACE DECOFLOOR 150 HARDENER

Concentration:	100 %		
Uses:	Professional exclusive use. For treating concrete, steel and other surfaces.		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Work footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN 20347		
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.		
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident		

ACE DECOFLOOR 150 HARDENER

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid.

Colour: Yellowish.

Odour: Not applicable/Not available due to the nature/properties of the product.

Odour threshold: Not applicable/Not available due to the nature/properties of the product.

Melting point: Not applicable/Not available due to the nature/properties of the product.

Freezing point: Not applicable/Not available due to the nature/properties of the product.

Boiling point or initial boiling point and boiling range: ≥ 147 °C.

Flammability: Not applicable/Not available due to the nature/properties of the product.

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product.

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product.

Flash point: ≥ 355 °C.

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product.

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product.

pH: Not applicable/Not available due to the nature/properties of the product.

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product.

Solubility: Not applicable/Not available due to the nature/properties of the product.

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product.

Liposolubility: Not applicable/Not available due to the nature/properties of the product.

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product.

Vapour pressure: Not applicable/Not available due to the nature/properties of the product.

Absolute density: Not applicable/Not available due to the nature/properties of the product.

Relative density: 0.992.

Relative vapour density: Not applicable/Not available due to the nature/properties of the product.

Particle characteristics: Not applicable/Not available due to the nature/properties of the product.

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product.

Explosive properties: Not applicable/Not available due to the nature/properties of the product.

Oxidizing properties: Not applicable/Not available due to the nature/properties of the product.

Dropping point: Not applicable/Not available due to the nature/properties of the product.

Blink: Not applicable/Not available due to the nature/properties of the product.

ACE DECOFLOOR 150 HARDENER

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

Exposure to concentrations of solvent fumes above the work exposure limit can have negative effects (for example, irritation of the mucous membranes and respiratory system, adverse effects on the kidneys, liver, and the central nervous system). Among the symptoms are headaches, vertigo, fatigue, muscular weakness, drowsiness, and in extreme cases, unconsciousness.

Based on the properties of isocyanates and taking into account existing technical data on similar products, it appears that this product may cause irritation and / or acute awareness of the respiratory system, leading to an asthmatic condition, a wheezing and chest pressure. Therefore, sensitized individuals may show asthmatic symptoms when exposed to atmospheres containing concentrations below the level of exposure. Repeated exposure can lead to chronic respiratory diseases.

ACE DECOFLOOR 150 HARDENER

a) acute toxicity;

Product classified:

Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Inhalation) = 17 mg/l/4 h (Fumes)

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

ACE DECOFLOOR 150 HARDENER

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

ACE DECOFLOOR 150 HARDENER

14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Safety Data Sheet

Conforms to Regulation (EC) n° 1907/2006
(REACH), Anexo II – United Kingdom (UK)

ACE DECOFLOOR 150 HARDENER

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
74. Diisocyanates, $O = C = N - R - N = C = O$, where R is an aliphatic or aromatic hydrocarbon structure of unspecified length	1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s). 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless: (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: 'As from 24 August 2023 adequate training is required before industrial or professional use'. 3. For the purpose of this entry 'industrial and professional user(s)' means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks. 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum: (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s). (b) the training elements in points (a) and (b) of paragraph 5 for the following uses: - handling open mixtures at ambient temperature (including foam tunnels); - spraying in a ventilated booth; - application by roller; - application by brush; - application by dipping and pouring; - mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore;

Safety Data Sheet

Conforms to Regulation (EC) n° 1907/2006
(REACH), Anexo II – United Kingdom (UK)

ACE DECOFLOOR 150 HARDENER

- cleaning and waste;
- any other uses with similar exposure through the dermal and/or inhalation route;
- (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:
 - handling incompletely cured articles (e.g. freshly cured, still warm);
 - foundry applications;
 - maintenance and repair that needs access to equipment;
 - open handling of warm or hot formulations ($> 45^{\circ}\text{C}$);
 - spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers);
 - and any other uses with similar exposure through the dermal and/or inhalation route.
- 5. Training elements:
 - (a) general training, including on-line training, on:
 - chemistry of diisocyanates;
 - toxicity hazards (including acute toxicity);
 - exposure to diisocyanates;
 - occupational exposure limit values;
 - how sensitisation can develop;
 - odour as indication of hazard;
 - importance of volatility for risk;
 - viscosity, temperature, and molecular weight of diisocyanates;
 - personal hygiene;
 - personal protective equipment needed, including practical instructions for its correct use and its limitations;
 - risk of dermal contact and inhalation exposure;
 - risk in relation to application process used;
 - skin and inhalation protection scheme;
 - ventilation;

Safety Data Sheet

Conforms to Regulation (EC) n° 1907/2006
(REACH), Anexo II – United Kingdom (UK)

ACE DECOFLOOR 150 HARDENER

- cleaning, leakages, maintenance;
 - discarding empty packaging;
 - protection of bystanders;
 - identification of critical handling stages;
 - specific national code systems (if applicable);
 - behaviour-based safety;
 - certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
- additional behaviour-based aspects;
 - maintenance;
 - management of change;
 - evaluation of existing safety instructions;
 - risk in relation to application process used;
 - certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered;
 - spraying outside a spraying booth;
 - open handling of hot or warm formulations (> 45 °C);
 - certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

ACE DECOFLOOR 150 HARDENER

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law;

(b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates;

(c) national exposure limits for diisocyanates, if there are any;

(d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Classification codes:

Acute Tox. 3 : Acute toxicity (Inhalation), Category 3

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4

Eye Irrit. 2 : Eye irritation, Category 2

Resp. Sens. 1 : Respiratory sensitiser, Category 1

STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Skin Irrit. 2 : Skin irritant, Category 2

Skin Sens. 1 : Skin sensitiser, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards: On basis of test data

Health hazards: Calculation method

ACE DECOFLOOR 150 HARDENER

Environmental hazards: Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

PPE: Personal protection equipment.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.